



NEK606 RFOU POWER & INSTRUMENTATION MARINE CABLE



APPLICATION

RFOU flame retardant, halogen free power and instrumentation marine cables for fixed installation. Suitable for use in all conditions in a marine environment such as muddy, dry, wet and oily conditions meeting the requirements of NEK 606.

CABLE STANDARDS

IEC 60228 class 2
IEC 60092-353
IEC60754-1, 2
IEC60332-3/A
IEC61034-1, 2
Mud Resistant NEK606

CONSTRUCTION

Conductor: Copper Conductor
Insulation: EPR
Bedding: Halogen Free Mud Resistant Bedding
Armouring: Tinned copper wire braid
Sheath: Mud resistant sheath
Sheath Colour: **Black**

CHARACTERISTICS

Voltage Rating: Power Cable 600/1000 Volts
*Instrumentation Cable 150-250 Volts
Temperature Limits: -40°C (fixed installation) to +90°C
Minimum Bending Radius: As per cable manufacturer datasheet

CORE IDENTIFICATION

2 Core: **Brown** **Blue**
3 Core: **Brown** **Black** **Grey**
4 Core: **Brown** **Black** **Grey** **Blue**
5 Core & above: **White** numbered

For more information contact:
01642 241 133



NEK606 RFOU MARINE POWER CABLE - DIMENSIONS

CCC CODE	CONDUCTOR SIZE (MM ²)	STRANDING (MM)	NO. OF CORES	WEIGHT	OVERALL DIAMETER
RFOU2X1/5	1.5	7/0.53	2	317	14.4
RFOU3X1/5	1.5	7/0.53	3	349	15
RFOU4X1/5	1.5	7/0.53	4	397	15.9
RFOU7X1/5	1.5	7/0.53	7	370	18.2
RFOU12X1/5	1.5	7/0.53	12	545	23.6
RFOU2X2/5	2.5	7/0.67	2	373	15.5
RFOU3X2/5	2.5	7/0.67	3	417	16.1
RFOU4X2/5	2.5	7/0.67	4	479	17.1
RFOU7X2/5	2.5	7/0.67	7	657	19.9
RFOU12X2/5	2.5	7/0.67	12	1115	25.5
RFOU2X4	4	7/0.85	2	460	17.1
RFOU3X4	4	7/0.85	3	521	17.8
RFOU4X4	4	7/0.85	4	616	19
RFOU2X6	6	7/1.04	2	546	18.3
RFOU3X6	6	7/1.04	3	627	19.1
RFOU4X6	6	7/1.04	4	616	20.9
RFOU2X10	10	7/1.35	2	724	20.2
RFOU3X10	10	7/1.35	3	857	21.1
RFOU4X10	10	7/1.35	4	1009	22.5
RFOU2X16	16	7/1.70	2	957	22.7
RFOU3X16	16	7/1.70	3	1148	23.6
RFOU4X16	16	7/1.70	4	1370	25.6
RFOU3X25	25	19/1.35	3	1609	27.6
RFOU4X25	25	19/1.35	4	1770	27.9
RFOU3X35	35	19/1.53	3	2079	30.9
RFOU4X35	35	19/1.53	4	2271	30.8

NEK606 RFOU MARINE INSTRUMENTATION CABLE - DIMENSIONS

CCC CODE	CONDUCTOR SIZE (MM ²)	STRANDING (MM)	NO. OF CORES	WEIGHT (KG/KM)	OVERALL DIAMETER
*RFOU1X2X/75GY	0.75	24/0.20	1 Pair	206	11.4
*RFOU1X2X0.75BU	0.75	24/0.20	1 Pair	206	11.4
*RFOUC2X2X/75GY	0.75	24/0.20	2 Pair	413	17.1
*RFOUC2X2X/75BU	0.75	24/0.2	2 Pair	413	17.1
*RFOUC4X2X/75GY	0.75	24/0.20	4 Pair	340	16.8
*RFOU1X3X/75GY	0.75	24/0.20	1 Triple	223	11.8
*RFOU1X2X1/5GY	1.5	7/0.53	1 Pair	248	12.3
*RFOUC2X2X1/5GY	1.5	7/0.53	2 Pair	501	18.7
*RFOU1X3X1/5GY	1.5	7/0.53	1 Triple	273	12.8 0
*RFOU4X2X1/5GY	1.5	7/0.53	4 Pair	610	22.6
*RFOU8X2X1/5GY	1.5	7/0.53	8 Pair	1140	32.8
*RFOU12X2X1/5GY	1.5	7/0.53	12 Pair	1445	35

For more information contact:
01642 241 133



NEK606 RFOU MARINE CABLE – ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA (MM ²)	CONTINUOUS CURRENT RATING				MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C
	SINGLE CORE	2 CORE	3 AND 4 CORE	5 CORE	CLASS 2 COPPER CONDUCTOR
0.75	14	11	9	8	24.8
1	18	15	13	11	18.2
1.5	23	20	16	13	12.2
2.5	30	26	21	18	7.56
4	40	34	28	23	4.7
6	52	44	36	30	3.11
10	72	61	50	42	1.84
16	96	82	67	56	1.16
25	127	108	89	74	0.734
35	157	133	110	92	0.529

THE ABOVE IS IN ACCORDANCE WITH 18TH EDITION OF IET WIRING REGULATIONS

For more information contact:
01642 241133

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

